NMALIAM				Enter Assembly #	
Y PROJECTS	PRODUCT SEARCH	SYSTEM SEARCH	ASSEMBLY SEARCH	RATINGS CALCULATOR	
	RIALS 🔻 🔯 🔻	I	1	1 1	
□ Back					
Product Detail Repo	ort				
Company:	GAF				
Trade Name: Document Link:	EnergyGuard				
Comments:	none Max total thickness is 1	2 in (205 mm)			
Approved Uses					
Insulation (Board St	tock)				
Insulation (Board St Material:		urate/polyurethane			
		urate/polyurethane			
Material:	polyisocyan flat 48.00 × 48.00	) in			
Material: Board Profile: Board Sizes:	polyisocyan flat 48.00 × 48.00 48.00 × 96.00	) in I in			
Material: Board Profile: Board Sizes: Top Facers:	polyisocyan flat 48.00 x 48.00 48.00 x 96.00 organic felt, g	l in l in lass reinforced			
Material: Board Profile: Board Sizes: Top Facers: Bottom Facers:	polyisocyan flat 48.00 x 48.00 48.00 x 96.00 organic felt, g organic felt, g	in in lass reinforced lass reinforced			
Material: Board Profile: Board Sizes: Top Facers: Bottom Facers: Min Density:	polyisocyan flat 48.00 × 48.00 48.00 × 96.00 organic felt, g organic felt, g 0.0000 lb/ft3	in in lass reinforced lass reinforced			
Material: Board Profile: Board Sizes: Top Facers: Bottom Facers:	polyisocyan flat 48.00 x 48.00 48.00 x 96.00 organic felt, g organic felt, g	in in lass reinforced lass reinforced			

Terms of Use · Privacy Policy · Compatibility

© 2005-2021 FM Approvals LLC. All rights reserved.



4.1.21098.1